

AEGIS® Precision Wound Condensate Polishing Septa with Stainless Steel Hardware

Graver's Aegis wound septa are one of the critical components in a precoat system and designed to provide an optimum surface for Gravex Powdex® resin. Aegis precision wound septa are available in a variety of sizes and hardware configurations to meet every application requirement.

2", 2¼", 2¾" Precoatable Elements

Aegis 2 – 2¾ inch (50 mm to 60 mm) wound filter Septa are designed for maximum durability and strength with the optimum precoat surface. Manufactured with stainless steel core and end connections, Aegis Septa have been the standard in precoat installations for over four decades.

1" Precoatable Elements

Aegis wound Septa are now also available in a 1-inch (25 mm) version that is easily installed in top tube sheet vessels with little or no equipment modifications.

Maintenance-free after installation, Aegis Septa provide long-lasting, dependable and economical protection of steam generators in both nuclear and fossil fuel operations.

When used with precoat materials such as Graver's Powdex resins, Aegis wound septa will deliver the highest purity water under a variety of influent conditions.

Three yarn PLC controlled winding pattern used by Graver Technologies' assures that each element has the optimum surface and filtration characteristics with uniform low-pressure drop and surface precoatability. Each element precoats evenly throughout the vessel, providing a maximum precoat cycle time and optimum water chemistry. Manufactured in the USA under an ISO 9001:2000 quality assurance system, Aegis Septa have been consistently improved by Graver for precoat condensate systems for more than 50 years and are the worldwide standard for this application.



SPECIFICATIONS 1", 2", 2¼", 2¾" WOUND FILTER ELEMENTS

Standard Lengths	50" to 80" (1,270 to 2,030 mm) Custom lengths also available
Element Construction (1" only)	Wound virgin polypropylene yarn
Element Construction (2", 2¼", 2¾")	Wound virgin yarns polypropylene and carbon fibers
Seal Mechanism (1" only)	Single Open End threaded stainless steel end fitting
Seal Mechanism (2", 2¼", 2¾")	Single Open End (Sealfast™/Ecoloc™) Flanged Double Open End (EPDM Flat Gaskets)
Hardware	Stainless steel-end fitting and a one piece core with integrated lock seam
Clean Pressure Drop (1" only)	1 to 3 psid (0.1 to 0.2 bar) with precoat at rated flux at 120°F (49°C)
Clean Pressure Drop (2", 2¼", 2¾")	0.5 to 4 psid (0.03 to 0.28 bar) with precoat at rated flux at 120°F (49°C)
Backwash (precoat service)	Recommended 20 to 22 psig differential (1.3 to 1.5 bar); maximum 27 psig (1.8 bar)
Recommended Flow (with precoat)	1.5 to 4.0 gpm (5.7 to 15.1 lpm) per square foot of element surface area
Maximum Operating Temperature	Polypropylene: 180°F (82°C) Carbon: 350°F (177°C)

AEGIS® Precision Wound Condensate Polishing Septa

with Stainless Steel Hardware

RECOMMENDED FLOW RATES PER ELEMENT (PRECOAT)

Element Size	50" (1,270 mm)	60" (1,520 mm)	70" (1,780 mm)	80" (2,030 mm)
1" (25 mm) Element				
Minimum Flow Rate (gpm/lpm)	1.6 / 6.1	2.0 / 7.6	2.2 / 8.3	2.5 / 9.5
Maximum Flow Rate (gpm/lpm)	4.4 / 16.7	5.2 / 19.7	6.1 / 23.1	7.0 / 26.5
2" (51 mm) Element				
Minimum Flow Rate (gpm/lpm)	3.3 / 12.5	4.0 / 15.1	4.6 / 17.4	5.3 / 20.1
Maximum Flow Rate (gpm/lpm)	8.8 / 33.2	10.4 / 39.6	12.4 / 46.0	14.0 / 52.8
2½" (57 mm) Element				
Minimum Flow Rate (gpm/lpm)	3.7 / 13.9	4.4 / 16.6	5.1 / 19.3	5.9 / 22.3
Maximum Flow Rate (gpm/lpm)	9.8 / 37.0	11.8 / 44.6	13.7 / 51.8	15.7 / 59.3
2¾" (60 mm) Element				
Minimum Flow Rate (gpm/lpm)	3.9 / 14.7	4.7 / 17.8	5.3 / 20.1	6.2 / 23.5
Maximum Flow Rate (gpm/lpm)	10.4 / 39.4	12.4 / 46.9	14.4 / 54.5	16.4 / 62.1

Features

- Stainless steel core and end fittings
- High surface area
- Designed specifically for plants that need to increase condensate flow while maintaining high purity condensate and smooth, consistent precoats
- The first large diameter septa designed for use with difficult thin-layer precoating techniques
- Manufactured in Graver's ISO certified state of the art facility with PLC controlled winding of 100% polypropylene, prewashed yarn
- Capable of supporting power upgrades by installing increased diameter septa to reduce system flux rate with increased precoat contact time and longer run length
- Carbon fiber available for high temperature applications

Superior Products & Global Reach

Graver is the global leader in high purity and condensate water treatment for power generation applications. Including both ion exchange and backwashable septa and filters.

Our innovative technology and products enable our customers to consistently meet today's tougher requirements for purity.

Graver's products treat more than 6.5 billion gallons of process water every day in over 38 countries. Over 75 percent of the nuclear powered generation plants, worldwide, use our technology. Graver has achieved this by consistently delivering dependable, high performance technology and products.

Whether your business is around the corner or around the world, Graver Technologies can support you with superior products and services.

For more information

Graver Technologies
Customer Service:
800.533.6623
E-mail: info@gravertech.com
Website: www.gravertech.com

United States Graver Technologies, LLC

200 Lake Drive
Glasgow, DE 19702 USA
800.533.6623
Phone: (302) 731.1700
Fax: (302) 731.1707

China Graver Technologies, LLC

RM 16D, Bldg. B
No.1118, Changshou RD
Shanghai, China 200042
Phone: (86) 21.5238.6576.608
Fax: (86) 21.5238.6579

Europe Graver Technologies, LLC

Koenigstrasse, 10c
D-70173 Stuttgart, Germany
Phone: (49) 711.3154.7160
Fax: (32) 61.32.9724



Graver Technologies

 A member of The Marmon Group
 A Berkshire Hathaway Company

All information and recommendations appearing in this bulletin concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Graver Technologies as to the effects of such use or the results to be obtained. Graver Technologies assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations. Aegis and Powdex are registered trademarks and Sealfast and Ecoloc are trademarks of Graver Technologies.



ISO 9001:2000
FM 38860