



Graver Technologies

Filtration | Separation | Purification

GSTACK Series Filter Housings

Lenticular Depth Filter Housings

Sanitary Housing, designed for use with Graver GSTACK Series Depth Filter Modules. GSTACK housings feature highly polished finish, sanitary fittings, vent connection, and no internal threads to meet the needs of high purity applications. The vertical configured housings are constructed of all 316L SS materials as standard in sizes to hold from 1 to 4 modules. The split dome in the 3 and 4 high allow flexibility to run different number of modules and also facilitates complete cleaning when disassembled.

Features–Benefits

- Accepts flat gasket or o-ring style lenticular filter elements
- Select from 2 diameters to accept either 12" or 16" modules
- 316L stainless steel with 180 grit finish
- 1.5" Sanitary tri-clamp Inlet & Outlet with 90 deg elbows
- Split dome for size flexibility and easy cleaning
- 0-60 psi stainless steel non-sanitary gauge
- V-Band Clamp Closure
- 60 PSIG Design Pressure
- EPDM Elastomers/Gaskets
- Non-Adjustable Legs with foot pads
- Top Vent

Product Specifications

Construction: 316 L Stainless Steel wetted parts

Shell Gasket Standard: EPDM

Optional Gaskets: Buna-N, Neoprene, Viton, Silicone, Teflon Encapsulated Silicone

Operating Parameters

Maximum operating pressure: 100 psig (6.9 bar) @ 200°F (93°C) in aqueous solutions
175°F (79°C) for oil based solutions

Flow Rate: 1 GPM/ft² of media surface area



Available Options

- Electropolish or <30 Ra polish for liquid contact parts
- ASME Code available
- Drains

Typical Applications

- Pharmaceuticals
- Chemicals
- Cosmetics
- Food and beverage

GSTACK Housing Nomenclature Information

GSH	12	03	FG	TC1.5	E	-EP
Model GSTACK Series		# of Modules	Adapter Style	Inlet/Outlet	Gasket	Options
Module Diameter		01 1	OR O-Ring	TC1.5 1.5" Tri-clamp (for 12")	S Silicone	EP Electropolished
12 12"		02 2	FG Flat gasket	TC2 2" Tri-clamp (for 16")	B Buna-N	D Drain
16 16"		03 3			E EPDM	G Pressure gauge
		04 4			V Viton	
					N Nitrile	
					T Teflon encap. silicone	

Example: GSH 1203FGTC1.5E-EP

GSTACK Housing Specifications

Model	Height		Base Width		Weight Empty		Filter Area*	
	(in)	(mm)	(in)	(mm)	(lbs)	(kg)	(ft ²)	(m ²)
GSH1201	39.6	1006	19.1	485	75	34.1	18.5	1.72
GSH1202	50.9	1293	19.1	485	93	42	37	3.44
GSH1203	62.1	1577	19.1	485	114	51.8	55.5	5.16
GSH1204	73.4	1864	19.1	485	132	59.7	64	5.95
GSH1601	39.6	1006	23.1	587	122	55.3	39.5	3.67
GSH1602	50.9	1293	23.1	587	145	65.7	79	7.34
GSH1603	62.1	1577	23.1	587	174	78.8	118.5	11.01
GSH1604	73.4	1864	23.1	587	197	89.2	158	14.68

* Based on 16 cell pack.
Dimensions include support legs.

For more information

Graver Technologies Customer Service: **1-888-353-0303**

Technical Support: **1-888-353-0303**

E-mail us at **info@gravertech.com**

Graver Technologies Europe (UK): **+44-1424-777791**

All information and recommendations appearing in this bulletin concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Graver Technologies as to the effects of such use or the results to be obtained. Graver Technologies assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

DISTRIBUTED BY:



Graver Technologies

200 Lake Drive
Glasgow,
DE 19702 U.S.A.

302-731-1700
800-249-1990
Fax: 302-369-0938

e-mail: info@gravertech.com
web site: www.gravertech.com

