

The Right Vessel For The Right Septa Choice

AEGIS® TurboGuard® Vessel Guide

TurboGuard® Vessel Information

Vessel selection is based upon first selecting the proper material of construction – either unlined carbon steel or 304 Grade Stainless Steel. The next critical component to select is the maximum operating design pressure – either 250 psig or 400 psig. The final design criteria to select is the maximum design flow rate for the filter. Utilizing the guide below the proper sized vessel is easily selected.



Vessel Sizing Information

- Vessels are sized for 60" TurboGuard filter elements
- For larger flow rates smaller units can be paralleled or stacked
- ASME Code Section VIII Division 1
- Horizontal or vertical mounting
- Flanged connections
- Designed for power plant use
- Inside to outside flow
- Filter elements contain no metal for ease in disposal
- Used in boiler condensate for both nuclear and fossil plants, heat recovering steam generators, Pre-Ro and combined cycle plants
- Easy access to filter elements
- No special maintenance required
- Design pressures to 400 psig
- Design temperatures to 180°F

Additional Information

- Filter elements are available in a variety of pore sizes to facilitate specific site conditions
- Units can be paralleled for additional flow capabilities
- Helps in lowering waste disposal costs



AEGIS® TurboGuard®

Vessel Guide

MATERIAL OF CONSTRUCTION	DESIGN PRESSURE (PSIG) @ 190°F	MAXIMUM FLOW RATES (GPM)*	NOMINAL HOUSING DIAMETER (IN)	ELEMENTS / HOUSING
CARBON STEEL (UNLINED)	250	1,200	14	3
		2,500	24	7
		5,000	36	14
		8,000	44	22
	400	1,200	14	3
		2,500	24	7
		5,000	36	14
		8,000	44	22
304 STAINLESS STEEL	250	1,200	14	3
		2,500	24	7
		5,000	36	14
		8,000	44	22
	400	1,200	14	3
		2,500	24	7
		5,000	36	14
		8,000	44	22

*Maximum flow rates must be verified based on operating conditions and process requirements.

Over 60 Years of Water Treatment Experience

For over 60 years Graver Water has manufactured equipment and offered services and parts for filters, clarifiers, deaerators, ion exchange, reverse osmosis systems, condensate polishing and more.

We design, engineer and manufacture water and wastewater treatment equipment and control systems for utility, industrial, commercial and municipal applications.

Let Graver provide the solution to your specific water quality needs with stand-alone equipment or a complete treatment system. We combine proven technology with innovative engineering solutions to resolve your treatment needs.



Customer Service Graver Water Systems

675 Central Avenue, Suite 3
New Providence, NJ 07974
P (908) 516.1400
F (908) 516.1401
W www.graver.com
W www.graver-nuclear.com

Customer Service Graver Technologies, LLC

P (800) 533.6623
E info@gravertech.com
W www.gravertech.com

United States Graver Technologies, LLC

200 Lake Drive
Glasgow, DE 19702 USA
P (800) 533.6623
P (302) 731.1700
F (302) 731.1707



MARMON A member of The Marmon Group
A Berkshire Hathaway Company

All information and recommendations appearing in this bulletin concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Graver Technologies as to the effects of such use or the results to be obtained. Graver Technologies assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations. Aegis and TurboGuard are registered trademarks of Graver Technologies.



Scan here to learn more
about Graver Technologies



ISO 9001
FM 38860

GTX-507
6/2013